



Shaking Waterbath



Technical features:

24/24 HOUR FUNCTION GUARANTEED

Outer case in stainless epoxy painted steel plate with acid rust-proof ground

Bath made in stainless steel 18/8 as per AISI 304

Glass-wool thermo-insulated walls and bottom

Inner movable trolley mounted on noiseless auto-lubricant wheels

Motion deriving from a motor combined with gear reduction motor

Shaking speed between 30/180 strokes per minute

Keyboard for speed setting

LCD display for direct reading of the number of stroke per minute

Heating via sheathed immersion resistors (1400 Watt)

Rack holder in stainless steel

Front control panel housing:

digital thermostat with microprocessor allowing P.I.D. auto-tuning control

safety thermostat with indicator lamp

shaking speed electronic controller and read-out

heating switch

shaking switch

Ext. dimensions (WxDxH) 870x380x350 mm = 36 kgs

Bath dimensions (WxDxH) 550x320x230 mm = 40 ltrs

Rack dimensions 400x270

CEI 62-25 Electric device – CE Marking - V.230 singlephase 50 Hz - 1500 Watt

model DUBNOFF (crosswise shaking motion)

model ROTABATH (orbital shaking motion)

3161 - Rack for 40 pcs. E-flasks 25 ml

3162 - Rack for 35 pcs. E-flasks 50 ml

3163 - Rack for 24 pcs. E-flasks 100 ml

3164 - Rack for 12 pcs. E-flasks 250 ml

3165 - Rack for 6 pcs. E-flasks 500 ml

3166 - Rack for test-tubes \varnothing on request

3167A - Lid

3167B - Cooling Coil

CV1 - Steel plate Stand

MADE IN ITALY