



## GLASSWARE DRYER



### Technical features:

Temperature range: Ambient +5°C to 150°C  
 Outer case in stove enamelled steel plate  
 Internal chamber in stainless steel case 18/8  
 AISI 304

Front door with 2 shutters, with interior in  
 stainless steel and exterior in stove  
 enamelled steel plate

Fan-forced air circulation via centrifugal fan

Outlet for the saturated air through a hole in  
 the body upper part

Heating via In Cr cable

Thermo-insulation through thick rock wool  
 panels

Internal shelves in stainless steel

Side Control Panel housing:

Digital thermostat with microprocessor allowing  
 P.I.D. auto-tuning control

Safety thermostat with visual alarm

Digital timer for cycle setting

Timer switch

Line switch

Safety fuses

V.380/3 +N.+Ground (or V.230/1)  
 CEI 62-25 Electric device – CE Marking

Model	internal dimensions (wxdxh) cm	total Volume ltrs	Shelves (tot.capacity)	external dimensions (wxdxh) cm	Watt
3671 A	90x60x150	810	4 (12)	130x 80x219	4500
3671 B	110x70x150	1155	4 (12)	150x 90x219	6000
3671 C	130x80x150	1560	4 (12)	170x100x219	7000

MADE IN ITALY