

SHAKER INCUBATOR with Temperature and Light control



Temperature range: from +5°C to 50°C

- outer case in painted steel rust proof
- inner case stainless steel AISI 304.
- inner transparent door
- external door (inside st.steel outside painted steel)
- heating through st.steel resistors.
- C.F.C. free refrigerating device
- overpowered compressor
- Fan for air circulation.

Lighting through n°6 Lamps (18 Watt) located in the inner part of the frontal door with pvc protection.

fan for lamps refreshing

built in SHAKING System (orbital or alternative motion on request) working range: 10 to 300 rpm

brushless motor

universal platform for clamps

max loading: 25 kgs

Control panel completed with:

- 'West 644' Programmer for Temperature & Light control
- 2 Min/max Temperature safety thermostats
- 2 switches for alternative lighting of 6 lamps (min.ave.max)
- switch for manual or programmed lighting
- shaker switch
- adjustable speed
- mains switch
- safety lamps
- fuses

Mod. C3TAL-S

int. Dim.: cm. 61L x 63P x 60H = Lt. 230

ext. Dim.: cm. 102L x 80P x 75H

shipping dimensions: cm.119x97x100 H

4 Revolving wheels

Monofase Voltage 230/50Hz - Kw. 1,6 – CE Marking

Options:

Memograph Digital Recorder M RSG40 4X input signals as per FDA 21CFR11

Clamps for flasks ml.: 50; 100; 250; 500; 1000; 2000

MADE IN ITALY