



STERILIZING DRYING OVEN

**Technical features:**

Temperature range: from Ambient +5°C to +250°C

Outer case in stainless epoxy painted steel plate with acid and rust-proof ground

Internal chamber in stainless steel as per AISI 304

External front door in enamelled steel and interior in stainless steel with silicone rubber gasket

Thermo insulation through thick rock wool panels

Heating provided by n.2 stainless steel sheathed resistors easy to replace

Fan powered circulation, through n.2 specific fans suitable for high temperature, ensure excellent thermal uniformity

Exhausting duct with movable cover on top

Control Panel mounted on the right side, housing :

-Digital thermoregulator PID autotuning

-Pt100 Sensor

-Over-temperature safety thermostat with alarm light

-Mains Switch

-Alarm light

-Safety fuses

230/1/50 Hz Electric system according to CEI 62-25 – CE Marking

Mod. C4

int. dimensions: cm. 64x65x100H = lt.416

ext.dimensions: cm.102x79x123H

n.3 st.steel Shelves

Options:

Timer

Key Lock

Castors kit

Mod. C5

int. dimensions: cm. 64x65x140H = lt.582

ext.dimensions: cm.102x79x164H

n.4 st.steel Shelves

Drying oven version

IQ-OQ Protocols - Temperature Protocol -

Temperature Recorder

Customized version upon request

MADE IN ITALY